

GE Healthcare

# Panda Warmers

A warm welcome for your precious newborns



# Multiple Solutions for Labor and Delivery



The Panda\* Warmers from GE combine advanced technologies with innovative features to deliver state-of-the-art thermoregulation while promoting family-centered care. And now available in three designs—Bedded, Freestanding and Wall Mount—to meet the specific needs of your care area. It's your choice!

	Wall Mount	Freestanding	Bedded
<b>Dimmable Observation Lights</b>	Y	Y	Y
<b>Full-Color Control Panel</b>	Y	Y	Y
<b>Handsfree Alarm Silence</b>	Y	Y	Y
<b>Data Trending Options</b>	Temp and SpO <sub>2</sub> <sup>†</sup>	Temp and SpO <sub>2</sub> <sup>†</sup>	Weight <sup>†</sup> , Temp and SpO <sub>2</sub> <sup>†</sup>
<b>Integrated SpO<sub>2</sub> Option</b>	Y	Y	Y
<b>Integrated Resuscitation Option</b>	N	Y	Y
<b>Aimable Procedure Light Option</b>	Y	Y	Y
<b>Integrated Weight Scale Option</b>	N	N	Y

<sup>†</sup>When optional feature is present.

## Panda Wall Mount Warmer

The Panda Wall Mount Warmer provides a stationary mounted solution to work with your bassinet, without compromising the thermal needs of your newborns. The unique design plans of your L&D require equipment that can be mounted in the most esthetically pleasing way. If you are using custom cabinetry or standard cabinetry to enclose the warmer, the Panda Wall Mount Warmer is intended to fit your specific design needs while providing the clinical features you require.



## Panda Freestanding Warmer

The Panda Freestanding Warmer provides all the features of a Bedded Warmer, but is designed to be used with your own bed or bassinet. Offering the clinical and workflow advantages of a Bedded Warmer with the freedom to move the thermal support of the Panda technology where and when you need it, the Panda Freestanding Warmer will complete your L&D and nursery warmer needs.



## Panda Bedded Warmer

The Panda Bedded Warmer offers the full capabilities found across the Panda Warmer portfolio. It can be configured with full resuscitation capability and SpO<sub>2</sub> monitoring, meeting clinical standards in a single configuration. It is intended to provide a complete warming environment with monitoring of critical newborn parameters.


# Simplified Care Advanced Features

## The right lights

Light levels are easily controlled to give you the right amount of light when it's needed. The *optional* integrated procedure light is easy-to-position and provides better lighting during procedures, reducing the need for additional external lighting.

## Hands-free alarm silence

Simply move your hand in front of the sensor to control the alarm. Helps maintain a clean environment and keeps the area quiet and soothing.



Hands-free alarm silence

## Warm-up with no nuisance alarms


Turn on the Panda Warmer in advance of delivery and your bed will be warm when the infant arrives. By eliminating nuisance alarms, we help keep the environment quiet and stress free for caregivers and parents.

## Brilliant full-color controls

Full-color control panel is readily accessible and easy to use. All patient information is vividly displayed on the monitor in real time.

## Heat where you need it

GE's innovative Hourglass Heat Profile bathes the baby in soothing warmth, and keeps the caregiver cool and comfortable while providing uniform coverage across the mattress.



Hourglass Heat Profile

# Options

## Integrated resuscitation


Always available with minimal setup for meeting NRP and ILCOR guidelines. Helps to standardize resuscitation protocols across the perinatal care area.

## Integrated SpO<sub>2</sub>

Monitors SpO<sub>2</sub> and heart rate without additional equipment. Captures data non-invasively. All baby parameters are displayed on the bed's full-color control panel.

## Integrated scale

Baby's first weight is available right at the bedside. So cute, parents might even take a picture!



Integrated Scale Display

# Nurses Balance Human Touch with Medical Technology

Today's labor and delivery care area has changed for clinicians. There's more patient information available at the point of care to aid decision making. With better equipment, you spend more time interacting with the parents, helping to make the birth a wonderful experience.



# Technical Specifications

## Mechanical

### Panda Bedded Warmer

- Height: 193–218 cm
- Width: 64 cm
- Depth: 119 cm
- Weight: 100 kg
- Mattress Size: 66 x 48 x 2 cm
- Bed Capacity: 14 kg
- Bed Tilt:  $\pm 12^\circ$  continuous tilt
- Maximum patient weight: 40 kg (88 lbs)

### Panda Freestanding Warmer

- Height: 195 cm
- Width: 85 cm
- Depth: 77 cm
- Weight: 43 kg

### Panda Wall Mount Warmer

- Height: 69 cm
- Width: 40 cm
- Depth: 49 cm
- Weight: 15 kg

### Accessories – Bedded Only

- Storage drawer package: 6.8 kg max load
- Instrument shelf: 3.6 kg max load

## Operating Environment

- Temperature: 18°C to 30°C
- Humidity: 5% to 75% non-condensing relative humidity
- Pressure: 70–106 kPa
- Air Velocity: up to 0.3 m/sec
- Water Ingress: IPX0

## Electrical Power Requirements

- 5.25 A @ 100v ~, 50/60 Hz
- 4.57 A @ 115v ~, 50/60 Hz
- 2.39 A @ 200v ~, 50/60 Hz
- 2.28 A @ 230v ~, 50/60 Hz
- 2.19 A @ 240v ~, 50/60 Hz

## Integrated Resuscitation Characteristics

- Input pressure: 40–75 psi (275–517 kPa)
- Minimum Input Flow: 70 lpm
- Vacuum Range: 0–150 mmHg
- Vacuum Accuracy:  $\pm 5\%$  of full scale
- Flow Range: 0–15 lpm
- Air/O<sub>2</sub> Blender Range: 21–100% O<sub>2</sub>
- Blender Accuracy:  $\pm 5\%$  O<sub>2</sub>

*Adjustable PIP (For T-Piece Resuscitation System only)*

- Maximum PIP: 45  $\pm$  5 cm H<sub>2</sub>O
- PIP Override: > 30  $\pm$  4 cm H<sub>2</sub>O
- Flow Capacity: 15 lpm

## Integrated SpO<sub>2</sub> Characteristics

Parameter	Masimo Rainbow SET®	Nellcor Oximax™
Measurement Range		
SpO <sub>2</sub>	30–100%	1–100%
Pulse Rate	25–240 bpm	20–300 bpm
SpO <sub>2</sub> Accuracy		
From 70–100%	$\pm 3$ digits for neonates	$\pm 3$ digits for neonates
Below 69%	Unspecified	Unspecified
Pulse Rate Accuracy		
No Motion	$\pm 3$ bpm	$\pm 3$ bpm
Motion	$\pm 5$ bpm	N/A

## System Performance

- Warmer expected: Approx. 8 years service life
- Heater Element: 360 Watts
- Patient temperature:  $\pm 0.3^\circ\text{C}$  @ 30°C measurement accuracy; to 42°C
- Observation Light: 2 dimmable 35W halogen bulbs: est. life 3000 hrs
- Procedure Light: Avg. 2000 lux (at nominal voltage); est. life 3000 hrs

### User control settings

- Patient Control: 34–37.5°C in 0.1° temperature increments
- Radiant heat power: 0–100% in 5% increments

### Irradiance

- Bedded Warmer 100% Heater Power: 31 mW/cm<sup>2</sup>
- Non-Bedded Warmer (at Highest Mattress Height Position): 100% Heater Power: 31 mW/cm<sup>2</sup>
- Heater Warmup Time at 100% Power: less than 3 minutes

### Weight scale performance

- Functional range: 300 g to 8 kg
- Accuracy:  $\pm 10$  g



Baby Temp (C)

Heater Power 100%

Mode Manual Baby

Pulse Rate

SpO2

My weight is... 7 lbs 8 oz

Back

GE

L/min

% O<sub>2</sub>

L/min

© 2013 General Electric Company – All rights reserved.

General Electric Company reserves the right to make changes in specifications and features shown herein, or discontinue the product described at any time without notice or obligation. Contact your GE Representative for the most current information.

GE and GE Monogram are trademarks of General Electric Company.

\*Panda is a trademark of General Electric Company.

Datex-Ohmeda, Inc., a General Electric company, doing business as GE Healthcare.

UK  
Tel : 0800 0329201

Germany  
Tel : 0800 1890461

Austria  
Tel : 0800 291888

Italy  
Tel : 0800 786947

Spain  
Tel : 0900 993620

France  
Tel : 0800 908719

Switzerland  
German

Tel : 0800 837279  
French  
Tel : 0800 837279

## About GE Healthcare

GE Healthcare provides transformational medical technologies and services that are shaping a new age of patient care. Our broad expertise in medical imaging and information technologies, medical diagnostics, patient monitoring systems, drug discovery, biopharmaceutical manufacturing technologies, performance improvement and performance solutions services help our customers to deliver better care to more people around the world at a lower cost. In addition, we partner with healthcare leaders, striving to leverage the global policy change necessary to implement a successful shift to sustainable healthcare systems.

Our “healthymagination” vision for the future invites the world to join us on our journey as we continuously develop innovations focused on reducing costs, increasing access and improving quality around the world. Headquartered in the United Kingdom, GE Healthcare is a unit of General Electric Company (NYSE: GE). Worldwide, GE Healthcare employees are committed to serving healthcare professionals and their patients in more than 100 countries. For more information about GE Healthcare, visit our website at [www.gehealthcare.com](http://www.gehealthcare.com).

GE Healthcare  
P.O. Box 900, FIN-00031 GE, Finland  
GE Direct United Kingdom: +44 (0)800 0329201

[www.gehealthcare.com](http://www.gehealthcare.com)



GE imagination at work